



TRANSflo CVT

Continuously Variable Transmission Fluid

Features & benefits

- Provides robust, durable performance
- Performance validated with extensive vehicle testing
- Extends integrity and operational life of critical components
- Anti-shudder durability and friction protection



Specifications

■ Suitable for use

Specification	TRANSflo CVT
Audi Multitronic	■
Chery CVT	■
Daihatsu AMMIX CVTF-DC, CVTF-DFC, CVTF-DFE	■
Daihatsu Fluid TC	■
Dodge/Chrysler/Jeep/Mopar CVT+4®	■
Dodge/Jeep/Chrysler NS-2	■
Fiat Tutela Car CVT N.G	■
Fujijyuuko i-CVTF FG	■
GM/Saturn DEX-CVT, GM 1940713 & 1940714	■
Honda CVT, HMMF, & Z-1 ¹	■
Honda HCF-2	■
Hyundai/Kia SP CVT-1, SP III ²	■
Idemitsu CVTF-EX1	■
Lexus Fluid TC, FE	■
Mazda CVTF 3320	■
MG Rover EM-CVT	■
Mini Cooper (BMW) EZL 799, EZL 779A & ZF CVT V1	■
Mitsubishi (DiaQueen) ATF SP-III ²	■
Mitsubishi CVTF ECO J4	■
Mitsubishi (DiaQueen) CVTF J1, J4, J4+	■
Nissan N-CVT, NS-1, NS-2, NS-2V & NS-3	■
Punch CVTF-EX1	■
Renault CVT CK/SK/FK	■
Renault Elf Matic CVT	■
Subaru ECVT, iCVT, iCVT FG	■
Subaru Lineartronic chain CVT, CVT II; High Torque (HT) CVTF & CV-30	■
Subaru NS-2	■
Suzuki CVTF Green 1 (Shell Green 1V), Green 2	■
Suzuki CVTF 3320, 4401, TC	■
Suzuki NS-2	■
Toyota CVTF FE, TC	■
Volvo CVT 4959	■
VW/Audi TL 52516 (G 052 516), 52180 (G 052 180 A2)	■
Zotye CVTs	■

¹ CVT without starting clutch

² CVT model only

TRANSflo CVT is a synthetic transmission fluid designed for continuous variable transmission. This multi-vehicle CVT fluid provides excellent anti-shudder durability and friction protection to keep your transmission running smoothly.

TRANSflo CVT fluid meets the performance requirements of vehicles equipped with push-belt and chain CVTs, such as Nissan, Toyota, Subaru, Mitsubishi, Suzuki, and Honda.

TRANSflo CVT is not to be used in DCT applications.

Specifications Continued

Specification	TRANSflo CVT
Toyota THSII / Toyota Prius	■
Ford Escape Hybrid with e-CVT	■
Honda Immd	■
Jatco CVT 8 Hybrid	■
Mazda SKYACTIVE-HYBRID	■

Typical results

Test Method	TRANSflo CVT
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	33.3 7.1
VISCOSITY INDEX (D2270)	185
COLOUR	Green
DENSITY @ 15°C (D4052), kg/L	0.847
POUR POINT (D97), °C	-51
FLASH POINT (D93), °C	197
BROOKFIELD @ -40°C (D2983), cP	14,000